

Dimensions d'encombrement (mm)				Charge de base (KN)		Vitesse maximum (rpm)			Désignation	Autres dimensions		Distance des points de travail (mm)	Cotes de montage (mm)				Masse (kg)
						Z, ZZ, RS, 2RS types	Type ouvert						d _a (Min.)	d _a (Max.)	D _a (Max.)	r _a (Max.)	
d	D	B	r (mm)	C _r	C _{or}		Graisse	Huile		d1	D1	a					Approx
10	30	14	0.6	7.41	4.3				3200A	17.7	23.6	18	15		25	0.6	0.051
	30	14	0.6	7.41	4.3	16000			3200-2RS	15.8	25	18	15	15.5	25	0.6	0.051
	30	14	0.6	7.41	4.3	16000			3200A-ZZ	17.7	25	18	15		25	0.6	0.051
12	32	15.9	0.6	10.1	5.6		15000	20000	3201A	19.1	26.5	20	17		27	0.6	0.058
	32	15.9	0.6	10.1	5.6	15000			3201-2RS	17.2	27.7	20	17	17	27.7	0.6	0.058
	32	15.9	0.6	10.1	5.6	15000			3201A-ZZ	19.1	27.7	20	17	0	27.7	0.6	0.058
15	35	15.9	0.6	11.2	6.8		12000	17000	3202A	22.1	29.5	22	20		30	0.6	0.066
	35	15.9	0.6	11.2	6.8	12000			3202-2RS	20.2	30.7	22	20	20	30.7	0.6	0.066
	35	15.9	0.6	11.2	6.8	12000			3202A-ZZ	22.1	30.7	22	20	0	30.7	0.6	0.066
	42	19	1	15.1	9.15		10000	15000	3302A	25.6	34.3	26	21		36	1	0.13
	42	19	1	15.1	9.15	10000			3302-2RS	23.7	35.7	26	21	23.5	36	1	0.13
17	40	17.5	0.6	14	8.65		10000	15000	3203A	25.2	33.6	25	22		35	0.6	0.096
	40	17.5	0.6	14	8.65	10000			3203-2RS	23.3	35	25	22	23	35	0.6	0.096
	40	17.5	0.6	14	8.65	10000			3203A-ZZ	25.2	35	25	22	0	35	0.6	0.096
	47	22.2	1	21.2	12.5		9500	14000	3303A	27.6	38.8	29	23		41	1	0.18
	47	22.2	1	21.2	12.5	9500			3303-2RS	25.7	40.2	29	23	25.5	41	1	0.18
	47	22.2	1	21.2	12.5	9500			3303A-ZZ	27.6	40.2	29	23	0	41	1	0.18
20	47	20.6	1	18.6	12		9000	13000	3204A	29.6	39.5	30	26		41	1	0.16
	47	20.6	1	18.6	12	9000			3204-2RS	27.7	40.9	30	26	27.5	41	1	0.16
	47	20.6	1	18.6	12	9000			3204A-ZZ	29.6	40.9	30	26	0	41	1	0.16
	52	22.2	1.1	22.1	14.3		8500	12000	3304A	31.8	42.6	32	27		45	1	0.22
	52	22.2	1.1	22.1	14.3	8500			3304-2RS	29.9	44	32	27	29.5	45	1	0.22
	52	22.2	1.1	22.1	14.3	8500			3304A-ZZ	31.8	44	32	27	0	45	1	0.22
25	52	20.6	1	20.3	14		8000	11000	3205A	34.6	44.5	33	31		46	1	0.18
	52	20.6	1	20.3	14	8000			3205-2RS	32.7	45.9	33	31	32.5	46	1	0.18
	52	20.6	1	20.3	14	8000			3205A-ZZ	34.6	45.9	33	31	0	46	1	0.18
	62	25.4	1.1	31.2	20.8		7500	10000	3305A	38.4	51.4	38	32		55	1	0.35
	62	25.4	1.1	31.2	20.8	7500			3305-2RS	35.7	53.4	38	32	35.5	55	1	0.35
	62	25.4	1.1	31.2	20.8	7500			3305A-ZZ	38.4	53.4	38	32	0	55	1	0.35
30	62	23.8	1	28.1	20		7000	9500	3206A	41.4	53.2	38	36		56	1	0.29
	62	23.8	1	28.1	20	7000			3206-2RS	38.7	55.2	38	36	38.5	56	1	0.29
	62	23.8	1	28.1	20	7000			3206A-ZZ	41.4	55.2	38	36	0	56	1	0.29
	72	30.2	1.1	41	28.5		6300	8500	3306A	39.8	64.1	44	37		65	1	0.53
	72	30.2	1.1	45.7	42.5		6300	8500	3306E	39.8	64.1	44	37		65	1	0.59
	72	30.2	1.1	41	28.5	6300			3306-2RS	39.8	64.1	44	37	39.5	65	1	0.53
	72	30.2	1.1	45.7	42.5	6300			3306E-2RS	39.8	64.1	44	37	39.5	65	1	0.59
	72	30.2	1.1	41	28.5	6300			3306A-ZZ	39.8	64.1	44	37	39.5	65	1	0.53
	72	30.2	1.1	45.7	42.5	6300			3306E-ZZ	39.8	64.1	44	37	39.5	65	1	0.59
35	72	27	1.1	37.1	27.5		6000	8000	3207A	48.1	61.9	45	42		65	1	0.44
	72	27	1.1	37.1	27.5	6000			3207-2RS	45.4	63.9	45	42	45	65	1	0.44
	72	27	1.1	37.1	27.5	6000			3207A-ZZ	48.1	63.9	45	42	0	65	1	0.44
	80	34.9	1.5	48.8	34		5600	7500	3307A	44.6	70.1	49	44		71	1.5	0.73
	80	34.9	1.5	53.9	51		5600	7500	3307E	44.6	70.1	49	44		71	1.5	0.79
	80	34.9	1.5	48.8	34	5600			3307-2RS	44.6	70.1	49	44	44.5	71	1.5	0.73
	80	34.9	1.5	53.9	51	5600			3307E-2RS	44.6	70.1	49	44	44.5	71	1.5	0.79
	80	34.9	1.5	48.8	34	5600			3307A-ZZ	44.6	70.1	49	44	44.5	71	1.5	0.73
80	34.9	1.5	53.9	51	5600			3307E-ZZ	44.6	70.1	49	44	44.5	71	1.5	0.79	
40	80	30.2	1.1	44.9	33.5		5600	7500	3208A	47.8	72.1	49	47		73	1	0.58
	80	30.2	1.1	48.4	48		5600	7500	3208E	47.8	72.1	49	47		73	1	0.64
	80	30.2	1.1	44.9	33.5	5600			3208-2RS	47.8	72.1	49	47	47.5	73	1	0.59
	80	30.2	1.1	48.4	48	5600			3208E-2RS	47.8	72.1	49	47	47.5	73	1	0.64
	80	30.2	1.1	44.9	33.5	5600			3208A-ZZ	47.8	72.1	49	47	47.5	73	1	0.58
	80	30.2	1.1	48.4	48	5600			3208E-ZZ	47.8	72.1	49	47	47.5	73	1	0.64
	90	36.5	1.5	59.2	43		5000	6700	3308A	50.8	80.1	56	49		81	1.5	0.95
	90	36.5	1.5	66	64		5000	6700	3308E	50.8	80.1	56	49		81	1.5	1.05
	90	36.5	1.5	59.2	43	5000			3308-2RS	50.8	80.1	56	49	50.5	81	1.5	0.95
	90	36.5	1.5	66	64	5000			3308E-2RS	50.8	80.1	56	49	50.5	81	1.5	1.05
45	85	30.2	1.1	47.5	38		5000	6700	3209A	52.8	77.1	52	52		78	1	0.63
	85	30.2	1.1	50.1	53		5000	6700	3209E	52.8	77.1	52	52		78	1	0.69
	85	30.2	1.1	47.5	38	5000			3209-2RS	52.8	77.1	52	52	52.5	78	1	0.63
	85	30.2	1.1	50.1	53	5000			3209E-2RS	52.8	77.1	52	52	52.5	78	1	0.69
	85	30.2	1.1	47.5	38	5000			3209A-ZZ	52.8	77.1	52	52	52.5	78	1	0.63
	85	30.2	1.1	50.1	53	5000			3209E-ZZ	52.8	77.1	52	52	52.5	78	1	0.69
	100	39.7	1.5	72.1	73.5		4500	6000	3309	63.8	86.3	64	54		91	1.5	1.4
50	90	30.2	1.1	47.5	39		4800	6300	3210A	57.8	82.1	56	57		83	1	0.66
	90	30.2	1.1	52.8	58.5		4800	6300	3210E	57.8	82.1	56	57		83	1	0.74
	90	30.2	1.1	47.5	39	4800			3210-2RS	57.8	82.1	56	57	57.5	83	1	0.66
	90	30.2	1.1	52.8	58.5	4800			3210E-2RS	57.8	82.1	56	57	57.5	83	1	0.74
	90	30.2	1.1	47.5	39	4800			3210A-ZZ	57.8	82.1	56	57	57.5	83	1	0.66
	90	30.2	1.1	52.8	58.5	4800			3210E-ZZ	57.8	82.1	56	57	57.5	83	1	0.74
	110	44.4	2	88	96.5		4000	5300	3310	73.3	97	73	60		100	2	1.95
55	100	33.3	1.5	57.2	67		4300	5600	3211	70.4	88.3	64	64		91	1.5	1.05
	120	49.2	2	95.2	108		3800	5000	3311	81	110	80	65		110	2	2.55
60	110	36.5	1.5	72.1	85		3800	5000	3212	78	98.3	71	69		101	1.5	1.4
	130	54	2.1	112	127		3400	4500	3312	87.2	115	86	72		118	2	3.25
65	120	38.1	1.5	78.1	95		3600	4800	3213	83.7	105	76	74		111	1.5	1.75

Dimensions d'encombrement (mm)				Charge de base (KN)		Vitesse maximum (rpm)			Désignation	Autres dimensions		Distance des points de travail (mm)	Cotes de montage (mm)				Masse (kg)
d	D	B	r (mm)	C _r	C _{or}	Z, ZZ, RS, 2RS types	Type ouvert			d1	D1		a	d _a (Min.)	d _a (Max.)	D _a (Max.)	
							Graisse	Huile									
75	160	68.3	2.1	157	186		2600	3600	3315	106	139	107	87		148	2	6.15
80	140	44.4	2	101	134		2800	3800	3216	102	127	91	90		130	2	2.65
	170	68.3	2.1	176	212		2400	3400	3316	113	148	112	92		158	2	6.95
85	150	49.2	2	110	146		2600	3600	3217	107	133	97	95		140	2	3.4
	180	73	3	194	240		2200	3200	3317	120	157	119	99		166	2.5	8.3
90	160	52.4	2	128	173		2400	3400	3218	115	143	104	100		150	2	4.15
	190	73	3	220	285		2000	3000	3318	128	169	125	104		176	2.5	9.25
95	170	55.6	2.1	147	204		2200	3200	3219	124	154	111	107		158	2	5
	200	77.8	3	238	315		1900	2800	3319	135	178	133	109		186	2.5	11
100	180	60.3	2.1	157	220		2000	3000	3220	129	160	118	112		168	2	6.1
	215	82.6	3	255	355		1800	2600	3320	142	187	139	114		201	2.5	13.5
110	200	69.8	2.1	190	270		1900	2800	3222	143	178	132	122		188	2	8.8
	240	92.1	3	292	425		1700	2400	3322	155	205	153	124		226	2.5	19