

Dimensions d'encombrement (mm)												Charge de base (kN)		Vitesse max. (rpm)		Désignation		Cotes de montage (mm)			Masse (kg) Approx.	
d	D	H	r _{1,2} min	d ₁	D ₁	D ₂	D ₃	C	H ₁	R	S	Cr	Cor	Graisse	Huile	Butée	Contre-plaque	d _a (min)	D _a (max)	r _a (max)	Butée	Contre-plaque
12	28	11.4	0.6	28	14	20	30	3.5	13	25	11.5	13.3	19	6000	8000	53201	U201	22	20	0.6	0.033	0.012
15	32	13.3	0.6	32	17	24	35	4	15	28	12	16.5	25	5300	7000	53202	U202	25	24	0.6	0.049	0.014
17	35	13.2	0.6	35	19	26	38	4	15	32	16	17.2	27.5	5000	6700	53203	U203	28	26	0.6	0.056	0.015
20	40	14.7	0.6	40	22	30	42	5	17	36	18	22.5	37.5	4500	6000	53204	U204	32	30	0.6	0.082	0.02
25	47	16.7	0.6	47	27	36	50	5.5	19	40	19	27.6	50	4000	5300	53205	U205	38	36	0.6	0.12	0.032
30	52	17.8	0.6	52	32	42	55	5.5	20	45	22	25.5	47.5	3600	4800	53206	U206	43	42	0.6	0.14	0.038
	60	22.6	1	60	32	45	62	7	25	50	22	37.7	65.5	2800	3800	53306	U306	48	45	1	0.27	0.056
35	62	19.9	1	62	37	48	65	7	22	50	24	35.1	67	3000	4000	53207	U207	51	48	1	0.22	0.057
	68	25.6	1	68	37	52	72	7.5	28	56	24	49.4	88	2400	3400	53307	U307	55	52	1	0.38	0.084
40	68	20.3	1	68	42	55	72	7	23	56	28.5	46.8	98	2800	3800	53208	U208	57	55	1	0.28	0.07
	78	28.5	1	78	42	60	82	8.5	31	64	28	61.8	112	2000	3000	53308	U308	63	60	1	0.55	0.12
	90	38.2	1.1	90	42	65	95	12	42	72	26	112	204	1700	2400	53408	U408	70	65	1	1.1	0.25
45	73	21.3	1	73	47	60	78	7.5	24	56	26	39	80	2600	3600	53209	U209	62	60	1	0.3	0.087
	85	30.1	1	85	47	65	90	10	33	64	25	76.1	140	1900	2800	53309	U309	69	65	1	0.66	0.17
	100	42.4	1.1	100	47	72	105	12.5	46	80	29	130	240	1600	2000	53409	U409	78	72	1	1.45	0.32
50	78	23.5	1	78	52	62	82	7.5	26	64	32.5	49.4	106	2400	3400	53210	U210	67	62	1	0.37	0.1
	95	34.4	1.1	95	52	72	100	11	37	72	28	88.4	173	1800	2600	53310	U310	77	72	1	0.97	0.23
	110	45.6	1.5	110	52	80	115	14	50	90	35	159	310	1500	2000	53410	U410	86	80	1.5	1.9	0.41
55	90	27.3	1	90	57	72	95	9	30	72	35	61.8	134	1900	2800	53211	U211	76	72	1	0.6	0.15
	105	39.3	1.1	105	57	80	110	11.5	42	80	30	104	208	1600	2200	53311	U311	85	80	1	1.4	0.28
60	95	28	1	95	62	78	100	9	31	72	32.5	62.4	140	1900	2800	53212	U212	81	78	1	0.66	0.16
	110	38.3	1.1	110	62	85	115	11.5	42	90	41	101	208	1600	2200	53312	U312	90	85	1	1.4	0.31
	130	54	1.5	130	62	95	135	16	58	100	34	199	400	1100	1600	53412	U412	102	95	1.5	3.1	0.71
65	100	28.7	1	100	67	82	105	9	32	80	40	63.7	150	1800	2600	53213	U213	86	82	1	0.73	0.18
	115	39.4	1.1	115	67	90	120	12.5	43	90	38.5	106	220	1500	2000	53313	U313	95	90	1	1.55	0.34
70	105	28.8	1	105	72	88	110	9	32	80	38	65	160	1800	2600	53214	U214	91	88	1	0.78	0.19
	125	44.2	1.1	125	72	98	130	13	48	100	43	135	300	1400	1900	53314	U314	103	98	1	2.1	0.41
	150	63.6	2	150	73	110	155	19.5	69	112	34	234	500	950	1400	53414	U414	118	110	2	5.5	1
75	110	28.3	1	110	77	92	115	9.5	32	90	49	67.6	170	1700	2400	53215	U215	96	92	1	0.81	0.21
	135	48.1	1.5	135	77	105	140	15	52	100	37	163	360	1200	1700	53315	U315	111	105	1.5	2.65	0.55
	160	69	2	160	78	115	165	21	75	125	42	251	560	900	1300	53415	U415	126	115	2	6.85	1.25
80	115	29.5	1	115	82	98	120	10	33	90	46	76.1	190	1700	2400	53216	U216	101	98	1	0.9	0.22
	140	47.6	1.5	140	82	110	145	15	52	112	50	159	360	1200	1700	53316	U316	116	110	1.5	2.75	0.57
	170	72.2	2.1	170	83	125	175	22	78	125	36	270	620	850	1200	53416	U416	133	125	2	8	1.4
85	125	33.1	1	125	88	105	130	11	37	100	52	97.5	250	1600	2200	53217	U217	109	105	1	1.2	0.29

Dimensions d'encombrement (mm)												Charge de base (kN)		Vitesse max. (rpm)		Désignation		Cotes de montage (mm)			Masse (kg) Approx.	
d	D	H	r _{1,2} min	d ₁	D ₁	D ₂	D ₃	C	H ₁	R	S	Cr	Cor	Graisse	Huile	Butée	Contre-plaque	d _a (min)	D _a (max)	r _a (max)	Butée	Contre-plaque
85	150	53.1	1.5	150	88	115	155	17.5	58	112	43	190	425	1100	1600	53317	U317	124	115	1.5	3.55	0.81
90	135	38.5	1.1	135	93	110	140	13.5	42	100	45	119	300	1500	2000	53218	U218	117	110	1	1.7	0.42
	155	54.6	1.5	155	93	120	160	18	59	112	40	195	465	1000	1500	53318	U318	129	120	1.5	3.85	0.84
	190	81.2	2.1	187	93	140	195	25.5	88	140	40	307	750	800	1100	53418	U418	149	140	2	11	1.9
100	150	40.9	1.1	150	103	125	155	14	45	112	52	124	320	1300	1800	53220	U220	130	125	1	2.2	0.5
	170	59.2	1.5	170	103	135	175	18	64	125	46	229	560	950	1400	53320	U320	142	135	1.5	5	0.95
	210	90	3	205	103	155	220	27	98	160	50	371	965	700	950	53420	U420	165	155	2.5	15	2.9
110	160	40.2	1.1	160	113	135	165	14	45	125	65	130	360	1200	1700	53222	U222	140	135	1	2.35	0.56
	190	67.2	2	187	113	150	195	20.5	72	140	51	276	720	850	1200	53322	U322	158	150	2	7.8	1.3
120	170	40.8	1.1	170	123	145	175	15	46	125	61	140	400	1100	1600	53224	U224	150	145	1	2.55	0.65
	210	74.1	2.1	205	123	165	220	22	80	160	63	325	915	800	1100	53324	U324	173	165	2	10.5	2
130	190	47.9	1.5	187	133	160	195	17	53	140	67	186	540	950	1400	53226	U226	166	160	1.5	3.95	0.9
140	200	48.6	1.5	197	143	170	210	17	55	160	87	190	570	950	1400	53228	U228	176	170	1.5	4.25	1.2