

Dimensions d'encombrement (mm)													Charge de base (kN)		Vitesse max. (rpm)		Désignation		Cotes de montage (mm)				Masse (kg) Approx.	
d	D	H	r _{1,2} min	r _{3,4} min	D ₁	D ₂	D ₃	B	C	H ₁	R	S	Cr	Cor	Graisse	Huile	Butée	Contre-plaque	d _a (max)	D _a (max)	r _a (max)	rb (max)	Butée	Contre-plaque
25	60	41.3	1	0.3	32	45	62	9	7	46	50	19.5	37.7	65.5	2800	3800	54306	U306	30	45	1	0.3	0.47	0.056
30	62	37.8	1	0.3	37	48	65	8	7	42	50	21	35.1	67	3000	4000	54207	U207	35	48	1	0.3	0.42	0.057
	68	38.6	1	0.6	42	55	72	9	7	44	56	25	46.8	98	2800	3800	54208	U208	40	55	1	0.6	0.56	0.07
	68	47.2	1	0.3	37	52	72	10	7.5	52	56	21	49.4	88	2400	3400	54307	U307	35	52	1	0.3	0.68	0.084
	78	54.1	1	0.6	42	60	82	12	8.5	59	64	23.5	61.8	112	2000	3000	54308	U308	40	60	1	0.6	1.05	0.12
35	85	56.3	1	0.6	47	65	90	12	10	62	64	21	76.1	140	1900	2800	54309	U309	45	65	1	0.6	1.25	0.17
	100	78.9	1.1	0.6	47	72	105	17	12.5	86	80	23.5	130	240	1600	2200	54409	U409	45	72	1	0.6	2.7	0.32
40	95	64.7	1.1	0.6	52	72	100	14	11	70	72	23	88.4	173	1800	2600	54310	U310	50	72	1	0.6	1.85	0.23
	110	83.2	1.5	0.6	52	80	115	18	14	92	90	30	159	310	1500	2000	54410	U410	50	80	1.5	0.6	3.55	0.46
45	90	49.6	1	0.6	57	72	95	10	9	55	72	32.5	61.8	134	1900	2800	54211	U211	55	72	1	0.6	1.15	0.15
50	110	70.7	1.1	0.6	62	85	115	15	11.5	78	90	36.5	101	208	1600	2200	54312	U312	60	85	1	0.6	2.6	0.31
65	140	86.1	1.5	1	82	110	145	18	15	95	112	45.5	159	360	1200	1700	54316	U316	80	110	1.5	1	5.05	0.57
	170	128.5	2.1	1	83	125	175	27	22	140	125	30.5	270	620	850	1200	54416	U416	80	125	2	1	14	1.4
70	150	92.5	1.5	1	88	115	155	19	17.5	105	112	39	190	425	1100	1600	54317	U317	85	115	1.5	1	6.35	0.81
80	210	159.9	3	1.1	103	155	220	33	27	176	160	43.5	371	965	700	950	54420	U420	100	155	2.5	1	26	2.9