

Type	Application ø		Matière	M x b	S + 0,2	Boitage	Emballage
	min.	max.					
ATE	27	30	W1	M8 x 55	1,5	250	250
ATE	30	33	W1	M8 x 55	1,5	250	250
ATE	33	36	W1	M8 x 60	2	250	250
ATE	36,5	39,5	W1	M8 x 65	2	250	250
ATE	39	42	W1	M8 x 60	2,5	100	100
ATE	40,5	43,5	W1	M8 x 65	2,5	100	100
ATE	42	45	W1	M8 x 65	2,5	100	100
ATE	45	48	W1	M8 x 80	2,5	100	100
ATE	47,5	50	W1	M8 x 60	2,5	100	100
ATE	48	51	W1	M8 x 60	2,5	50	50
ATE	49	52	W1	M8 x 65	2,5	50	50
ATE	52	54,1	W1	M8 x 65	2,5	50	50
ATE	53	56	W1	M8 x 65	2,5	50	50
ATE	55	58	W1	M8 x 70	2,5	50	50
ATE	57	59,1	W1	M8 x 70	2,5	50	50
ATE	58	61	W1	M8 x 80	2,5	50	50
ATE	61	64	W1	M8 x 80	2,5	50	50
ATE	67	71	W1	M8 x 90	3	50	50

### Matière

Vis: Acier classe 8.8 zingué blanc

Bande : Acier St34 (DIN 2393C)